



Housing No.	Shaft		Dimensions (mm)											Mounting Bolt	Weight (kg)	Labyrinth Seals	Bearing	Fixing Rings	End cover	O-Ring \varnothing * Length	Grease Qty First filling			
	da	db	Da	Ca	A	A1	A2	H	H1	H2	L	J	J1									N	N1	S
SD 2232 G	160	180	290	115	240	190	250	353	180	75	530	450	110	34	28	15	M24	78	TS 38-180	22232	2 x FR 290-17,5	ETS44	4 x 620	1,5 kg
SD 2234 G	170	190	310	122	260	210	270	375	190	80	560	480	120	34	28	10	M24	98	TS 40-190	22234	2 x FR 310-18	ETS48	4 x 660	2,0 kg
SD 2236 G	180	200	320	124	260	210	270	375	190	80	560	480	120	34	28	10	M24	98	TS 44	22236	2 x FR 320-19	ETS44	4 x 690	1,8 kg
SD 2238 G	190	210	340	132	280	230	290	411	210	85	610	510	130	42	35	10	M30	123	TS 48-210	22238	4 x FR 340-10	ETS48	4 x 730	2,3 kg
SD 2240 G	200	220	360	140	290	240	300	434	220	90	640	540	140	42	35	12	M30	139	TS 48	22240	2 x FR 360-21	ETS56	4 x 760	3,0 kg
SD 2244 G	220	240	400	148	310	260	315	474	240	95	700	600	150	42	35	12	M30	187	TS 56-240	22244	4 x FR 400-10	ETS56	4 x 830	3,4 kg
SD 2248 G	240	260	440	164	320	280	330	516	260	100	770	650	160	50	42	13	M36	221	TS 60-260	22248	2 x FR 440-22	ETS60	4 x 900	4,3 kg
SD 2252 G	260	280	480	181	350	310	360	591	300	110	830	710	190	50	42	22	M36	301	TS 64-280	22252	2 x FR 480-25,5	ETS72	4 x 970	7,0 kg
SD 2256 G	280	300	500	180	350	310	360	591	300	110	830	710	190	50	42	22	M36	301	TS 68-300	22256	2 x FR 500-25	ETS68	4 x 1040	6,2 kg
SD 2260 G	300	320	540	196	370	330	380	631	320	115	880	750	200	50	42	23	M36	339	TS 72-320	22260	2 x FR 540-28	ETS72	4 x 1100	7,7 kg
SD 2264 G	320	340	580	210	400	360	410	675	340	120	950	810	220	50	42	24	M36	415	TS 76-340	22264	2 x FR580-20	ETS76	4 x 1180	9,4 kg

These Housings can also be manufactured of ductile iron or cast steel. Special kevlar or felt seals on request.