



Housing for shaft end.
A Type

Housing for through shaft.
B Type

Housing Number	Shaft Ø mm	D	Dimensions (mm)								Bearing No.				Adapter Sleeve	Location Ring		Weight (kg)				
			a	b	c	g	h	L	w	m	S Bolt	R	x	K		K1	K2		Self. Align. Ball	Spherical Roller	Number	Qty.
TH 508	35	80	153	89	73	33,0	104,77	81	124	76	M20	25	22	53,97	28	51	1208 K / 2208 K	22208 K	H 208 / H 308	FR 80 X 7,5 / FR 80 X 10	2 1	4,1
TH 509	40	85	153	89	73	31,0	104,77	81	124	76	M20	25	24	53,97	28	51	1209 K / 2209 K	22209 K	H 209 / H 309	FR 85 X 6 / FR 85 X 8	2 1	4,2
THM 510	45	90	180	100	75	33,0	120,00	90	140	90	M20	25	25	53,00	30	50	1210 K / 2210 K	22210 K	H 210 / H 310	FR 90 X 6,5 / FR 90 X 10	2 1	4,8
THM 511	50	100	180	100	75	33,0	120,00	95	140	90	M20	25	26	53,00	30	52	1211 K / 2211 K	22211 K	H 211 / H 311	FR 100 X 6 / FR 100 X 8	2 1	5,0
THM 512	55	110	215	115	85	38,0	150,00	100	170	110	M20	25	28	68,00	32	60	1212 K / 2212 K	22212 K	H 212 / H 312	FR 110 X 8 / FR 110 X 10	2 1	9,7
THM 513	60	120	215	115	85	43,0	150,00	100	170	110	M20	25	30	68,00	32	60	1213 K / 2213 K	22213 K	H 213 / H 313	FR 120 X 10 / FR 120 X 12	2 1	8,6
THM 515	65	130	240	115	90	41,0	165,00	115	185	120	M20	30	31	68,00	32	65	1215 K / 2215 K	22215 K	H 215 / H 315	FR 130 X 8 / FR 130 X 10	2 1	11,5
THM 516	70	140	265	140	105	43,0	195,00	120	220	135	M20	30	36	78,00	40	75	1216 K / 2216 K	22216 K	H 216 / H 316	FR 140 X 8,5 / FR 140 X 10	2 1	16,2
THM 517	75	150	265	140	105	46,0	195,00	125	220	135	M20	30	40	78,00	40	75	1217 K / 2217 K	22217 K	H 217 / H 317	FR 150 X 9 / FR 150 X 10	2 1	16,2
THM 518	80	160	273	150	105	62,4	195,00	135	220	140	M20	30	42	78,00	40	75	1218 K / 2218 K	22218 K / 23218 K	H 218 / H 318 / H 2318	FR 160 X 16,2 / FR 160 X 11,2 / FR 160 X 10	2 2 1	19,6
THM 520	90	180	320	150	123	70,3	210,00	150	250	165	M24	35	45	93,00	45	90	2220 K	22220 K / 23220 K	H 320 / H 2320	FR 180 X 12,1 / FR 180 X 10	2 1	23,2
THM 522	100	200	360	160	130	80,0	240,00	160	280	180	M24	50	51	93,00	45	100	2222 K	22222 K / 23222 K	H 322 / H 2322	FR 200 X 13,5 / FR 200 X 10	2 1	27,0