



Item No.	Dimensions (mm)				Basic Load Ratings (N)		Limiting Speeds (RPM)		Mass (kg)
	d	D	B	r_{min}	Dynamic C_r	Static C_{Or}	Grease 2RS	Oil Open	
3200	10	30	14	0,6	7.800	4.550	19.700	22.000	0,05
3201	12	32	15,9	0,6	10.600	5.850	17.600	20.000	0,05
3202	15	35	15,9	0,6	11.800	7.100	16.700	19.000	0,07
3203	17	40	17,5	0,6	14.600	9.000	14.600	17.000	0,09
3204	20	47	20,6	1,0	19.600	12.500	12.100	15.000	0,15
3205	25	52	20,6	1,0	21.200	14.600	10.700	12.000	0,18
3206	30	62	23,8	1,0	30.000	21.200	9.000	9.500	0,29
3207	35	72	27	1,1	39.000	28.500	7.600	8.500	0,45
3208	40	80	30,2	1,1	48.000	36.500	6.700	7.500	0,59
3209	45	85	30,2	1,1	48.000	37.500	6.300	6.700	0,63
3210	50	90	30,2	1,1	51.000	42.500	5.900	6.300	0,68
3211	55	100	33,3	1,5	58.500	49.000	5.300	5.600	0,95
3212	60	110	36,5	1,5	72.000	61.000	4.750	5.000	1,27
3213	65	120	38,1	1,5	80.000	73.500	4.300	4.500	1,64
3214	70	125	39,7	2,0	83.000	76.500	4.300	4.500	1,80
3215	75	130	41,3	2,0	91.500	85.000	4.100	4.300	1,91
3216	80	140	44,4	2,0	98.000	93.000	3.800	4.000	2,45

For sealed bearings, add the suffix 2RS after the item number.