



## Angular Contact Ball Bearing 3200



Type	Dimensions (mm)				Basic radial load rating (N)		Speed (1/min)	
	d	D	B	m (kg)	Dynamic	Static	Limiting	Reference
<b>3200</b>	10	30	14	0,050	7800	4550	22000	24000
<b>3201</b>	12	32	15,9	0,051	10600	5850	20000	24000
<b>3202</b>	15	35	15,9	0,065	11800	7100	19000	20000
<b>3203</b>	17	40	17,5	0,093	14600	9000	17000	18000
<b>3204</b>	20	47	20,6	0,154	19600	12500	15000	16000
<b>3205</b>	25	52	20,6	0,178	21200	14600	12000	14000
<b>3206</b>	30	62	23,8	0,289	30000	21200	9500	12000
<b>3207</b>	35	72	27	0,446	39000	28500	8500	11000
<b>3208</b>	40	80	30,2	0,594	48000	36500	7500	10000
<b>3209</b>	45	85	30,2	0,628	48000	37500	6700	9000
<b>3210</b>	50	90	30,2	0,680	51000	42500	6300	8000
<b>3211</b>	55	100	33,3	0,954	58500	49000	5600	7500
<b>3212</b>	60	110	36,5	1,270	72000	61000	5000	7500
<b>3213</b>	65	120	38,1	1,640	80000	73500	4500	6700
<b>3214</b>	70	125	39,7	1,800	83000	76500	4500	6300
<b>3215</b>	75	130	41,3	1,910	91500	85000	4300	6000
<b>3216</b>	80	140	44,4	2,450	98000	93000	4000	5600