



Item No.	Dimensions (mm)					Basic Load Ratings (N)		Speed (1/min)	Mass
	d	D	T	D1	d1	Dynamic C _r	Static C _{0r}	Limiting	approx. (kg)
29240	200	280	48	236	265	655.000	2.650.000	2.000	8,15
29244	220	300	48	254	285	720.000	3.150.000	2.000	9,18
29248	240	340	60	282	320	1.040.000	4.500.000	1.700	16,10
29252	260	360	60	302	340	1.060.000	4.750.000	1.700	17,00
29256	280	380	60	322	360	1.120.000	5.100.000	1.500	19,20
29260	300	420	73	353	395	1.430.000	6.550.000	1.400	28,60
29264	320	440	73	372	415	1.500.000	6.950.000	1.300	30,30
29268	340	460	73	391	435	1.560.000	7.350.000	1.300	32,00
29272	360	500	85	423	475	1.900.000	8.800.000	1.200	46,50
29276	380	520	85	440	490	2.080.000	9.650.000	1.100	48,40
29280	400	540	85	460	510	2.120.000	10.200.000	1.100	51,20
29284	420	580	95	489	550	2.650.000	12.500.000	1.000	73,40
29288	440	600	95	506	570	2.650.000	13.400.000	1.000	74,00
29292	460	620	95	528	590	2.700.000	13.400.000	950	76,30
29296	480	650	103	556	620	2.800.000	14.600.000	900	90,90