



Item No.	Dimensions (mm)					Basic Load Ratings (N)		Speed (1/min)	Mass (kg)
	d	D	T	D1	d1	Dynamic C_r	Static C_{0r}	Limiting	approx.
29412	60	130	42	88	115	335.000	900.000	3.400	2,23
29413	65	140	45	94	125	380.000	1.020.000	3.400	3,03
29414	70	150	48	102	135	430.000	1.200.000	3.000	3,71
29415	75	160	51	108	140	490.000	1.370.000	2.800	4,40
29416	80	170	54	116	150	550.000	1.560.000	2.800	5,28
29417	85	180	58	123	160	600.000	1.730.000	2.600	5,89
29418	90	190	60	130	170	670.000	1.930.000	2.400	7,38
29420	100	210	67	142	185	830.000	2.450.000	2.200	10,00
29422	110	230	73	158	205	950.000	2.800.000	2.000	13,10
29424	120	250	78	172	220	1.120.000	3.350.000	1.800	16,30
29426	130	270	85	187	240	1.250.000	3.900.000	1.700	19,00
29428	140	280	85	194	250	1.290.000	4.050.000	1.700	21,90
29430	150	300	90	211	270	1.460.000	4.800.000	1.500	26,90
29432	160	320	95	224	285	1.660.000	5.300.000	1.400	31,60
29434	170	340	103	239	305	1.860.000	6.000.000	1.300	39,20
29436	180	360	109	253	320	2.080.000	6.800.000	1.300	46,20
29438	190	380	115	268	340	2.320.000	7.500.000	1.200	54,90
29440	200	400	122	282	360	2.550.000	8.500.000	1.100	64,70
29444	220	420	122	303	375	2.600.000	8.500.000	1.100	67,40
29448	240	440	122	321	400	2.700.000	9.500.000	1.100	73,50
29452	260	480	132	353	435	3.100.000	11.000.000	1.000	93,60
29456	280	520	145	380	470	3.650.000	12.900.000	900	121,00
29460	300	540	145	398	490	3.900.000	14.000.000	900	129,00
29464	320	580	155	432	525	4.300.000	15.600.000	800	158,00
29468	340	620	170	458	560	5.200.000	19.000.000	750	200,00