



Product No.	d (mm)	Dimensions (mm)																	Methric size	Bearing No.	Weight (kg)	Basic load ratings (N)		
		L	H	C	J	E	t	A2	A	P1	P2	P3	N	L1	U	B	S1	K				Max. Load	C _r	C _{or}
UCT 201-15	12	317	199	150	64	154	6	30	50	19	117	64	12	370	48,3	31,0	12,7	9	-	UC 201	6,4	7.650	12.800	6.650
UCT 202-15	15	317	199	150	64	154	6	30	50	19	117	64	12	370	48,3	31,0	12,7	9	-	UC 202	6,3	7.650	12.800	6.650
UCT 203-15	17	317	199	150	64	154	6	30	50	19	117	64	12	370	48,3	31,0	12,7	9	-	UC 203	6,3	7.650	12.800	6.650
UCT 204-15	20	317	199	150	64	154	6	30	50	19	117	64	12	370	48,3	31,0	12,7	9	-	UC 204	6,3	7.650	12.800	6.650
UCT 205-15	25	317	199	150	63	154	6	30	50	19	117	64	12	370	49,7	34,0	14,3	11	Tr20X4	UC 205	6,5	7.850	14.000	7.850
UCT 206-15	30	337	212	150	73	166	6	32	50	19	127	64	12	393	54,2	38,1	15,9	11	Tr20X4	UC 206	7,6	9.810	19.500	11.300
UCT 207-23	35	429	212	230	80	166	6	32	50	19	173	64	12	485	57,4	42,9	17,5	11	Tr20X4	UC 207	9,2	12.750	25.700	15.300
UCT 208-30	40	520	233	297	88	192	6	32	50	22	217	64	12	596	62,2	49,2	19,0	11	Tr20X4	UC 208	13	15.690	29.100	17.800
UCT 209-30	45	520	233	300	88	192	6	32	50	22	217	64	12	593	62,2	49,2	19,0	11	Tr20X4	UC 209	16	15.690	32.500	20.400
UCT 210-30	50	524	233	300	92	192	6	35	50	22	219	64	15	597	67,6	51,6	19,0	11	Tr20X4	UC 210	16	16.670	35.000	23.200
UCT 211-30	55	542	285	300	90	240	8	38	65	22	230	60	15	626	71,4	55,6	22,2	11	Tr20X4	UC 211	22	19.610	43.500	29.200
UCT 212-30	60	568	285	300	101	240	8	38	65	22	243	60	15	652	77,7	65,1	25,4	11	Tr20X4	UC 212	25	21.570	52.500	36.000
UCT 213-30	65	606	306	300	125	260	8	43	65	22	260	64	15	705	87,4	74,6	25,4	11	Tr20X4	UC 213	33	27.160	66.000	44.000
UCT 214-30	70	606	306	300	125	260	8	43	65	22	260	64	15	705	87,4	74,6	25,4	11	Tr20X4	UC 214	33	27.160	66.000	44.000
UCT 215-30	75	606	306	300	125	260	8	43	65	22	260	64	15	705	87,5	77,8	25,4	11	Tr20X4	UC 215	33	27.160	66.000	44.500