



Part No.	d		Dimensions (mm)									Bolt Size	Weight (kg)	
	mm		L	J	B	A ₂	A ₁	A	U	N	S			Q
UCF 201 SS	12		86	64	31,0	15	11	25,5	33,3	12,0	12,7	M6	M10	0,61
UCF 202 SS	15		86	64	31,0	15	11	25,5	33,3	12,0	12,7	M6	M10	0,61
UCF 203 SS	17		86	64	31,0	15	11	25,5	33,3	12,0	12,7	M6	M10	0,61
UCF 204 SS	20		86	64	31,0	15	11	25,5	33,3	12,0	12,7	M6	M10	0,61
UCF 205 SS	25		95	70	34,0	16	13	27,0	35,7	12,0	14,3	M6	M10	0,80
UCF 206 SS	30		108	83	38,0	18	13	31,0	40,2	12,0	15,9	M6	M10	1,07
UCF 207 SS	35		117	92	41,5	19	15	34,0	44,4	14,0	17,5	M6	M12	1,40
UCF 208 SS	40		130	102	49,2	21	15	36,0	51,2	16,0	19,0	M6	M12	1,80
UCF 209 SS	45		137	105	49,2	22	16	38,0	52,2	16,0	19,0	M6	M14	2,20
UCF 210 SS	50		143	111	52,0	22	16	40,0	54,6	16,0	19,0	M6	M12	2,40
UCF 211 SS	55		162	130	55,5	25	18	43,0	58,4	19,0	22,2	M6	M16	3,50
UCF 212 SS	60		175	143	65,0	29	18	48,0	68,7	19,0	25,4	M6	M16	4,20
UCF 213 SS	65		187	149	65,0	30	22	50,0	69,7	19,0	25,4	M6	M16	5,30
UCF 214 SS	70		193	152	74,6	31	22	54,0	75,4	19,0	30,2	M6	M16	5,90
UCF 215 SS	75		200	159	78,0	34	22	56,0	78,5	19,0	33,3	M6	M16	6,30
UCF 216 SS	80		208	165	82,5	34	22	57,0	83,3	23,0	33,3	M6	M20	7,30

Add suffix **SOLID** to order the solid base version.

Bearing Inserts:

Inner & Outer Races: AISI 440C Stainless

Cage: AISI 302 Stainless

Balls: AISI 440C Stainless

Seals: Rubber & AISI 302 Stainless

Set Screws: AISI 420 Stainless

Grease Nipple: AISI 304

Grease: Mobil FM 222 Food Grade

Housing:

AISI 304 Stainless, also available in a solid base version.

The solid base version has no cavities in the bottom where dirt can collect over time, thus making it easier to keep clean.