



Part No.	Dimensions (mm)				Mounting dimensions (mm)			Weight (g)
	$d4 \pm 0,25$	$D - 0,25$	$T - 0,05$	$M \pm 0,15$	$h + 0,4 + 0,1$	$t \pm 0,2$	$D1 + 0,12$	
DU10201.5TFW	10	20	1,5	15	1,5	1	20	2,7
DU12241.5TFW	12	24	1,5	18	1,5	1	24	3,9
DU14261.5TFW	14	26	1,5	20	2	2	26	4,3
DU16301.5TFW	16	30	1,5	23	2	1	30	5,8
DU18321.5TFW	18	32	1,5	25	2	1	32	6,3
DU20361.5TFW	20	36	1,5	28	3	1	36	8,1
DU22381.5TFW	22	38	1,5	30	3	1	38	8,7
DU24421.5TFW	24	42	1,5	33	3	1	42	10
DU26441.5TFW	26	44	1,5	35	4	1	44	11,4
DU28481.5TFW	28	48	1,5	38	4	1	48	13,7
DU32541.5TFW	32	54	1,5	43	4	1	54	17,1
DU38621.5TFW	38	62	1,5	50	4	1	62	21,5
DU40641.5TFW	40	64	1,5	52	4	1	64	22,3
DU42661.5TFW	42	66	1,5	54	4	1	66	23,5
DU487420.TFW	48	74	2	61	4	1,5	74	38,5
DU527820.TFW	52	78	2	65	4	1,5	78	41
DU629020.TFW	62	90	2	76	4	1,5	90	52
DU9013020.TFW	90	130	2	110	5	2	130	87

Tolerance: ISO 6525:1983

For special sizes: Please contact our sales department.

Also available in low-maintenance DX versions, which have a POM layer with lubrication pockets.