



Part No.	Dimensions (mm)													Bearings	Spring Washer	Screws G	Max. Speed (rpm)	Weight (kg)			
	da	H	H1	L2	A	A1	A2	L	b	H2	J1	J	S						X	N	D
PDN 306	30	50	100	210	226	171,5	140	160	40	18	150	130	6,1	9,5	15	72	6306 C3	6200-6306	4 x M6	9000	6,6
PDN 307	35	60	116	239	260	195,5	160	190	45	18	175	150	7,1	11	15	80	6307 C3	6200-6307	4 x M6	8500	9,2
PDN 308	40	60	121	298	315	255,5	214	190	52	20	225	150	9,1	9,4	15	90	6308 C3	6200-6308	4 x M6	7500	11,8
PDN 309	45	70	137	340	360	279,5	236	210	52	22	250	170	9,1	17,4	15	100	6309 C3	6200-6309	4 x M6	6700	15,0
PDN 310	50	70	142	360	377	311,5	266	210	60	25	275	170	9,1	10,4	15	110	6310 C3	6200-6310	6 x M6	6300	17,8
PDN 311	55	80	158	400	422	335,5	288	260	60	25	300	210	9,1	17,4	19	120	6311 C3	6200-6311	4 x M8	5600	27,5
PDN 312	60	80	165	437	460	383,5	334	260	70	25	340	210	9,1	10,9	19	130	6312 C3	6200-6312	6 x M8	5000	32,0
PDN 313	65	95	185	470	492	402,5	349	280	70	25	360	230	10,1	16,9	19	140	6313 C3	6200-6313	6 x M8	4800	34,0
PDN 314	70	95	190	490	512	420,5	365	290	70	25	380	230	10,1	16,9	19	150	6314 C3	6200-6314	6 x M8	4500	37,0
PDN 315	75	100	200	508	547	448,5	389	320	80	30	400	260	11,1	10,9	19	160	6315 C3	6200-6315	6 x M8	4300	48,0
PDN 316	80	112	220	525	556	466	403,5	320	80	30	420	260	11,1	9,4	19	170	6316 C3	6200-6316	6 x M10	3800	51,0
PDN 317	85	112	225	559	590	486	422,5	350	80	30	440	290	11,1	15,5	19	180	6317 C3	6200-6317	6 x M10	3600	65,0
PDN 318	90	112	230	575	605	510	446,5	350	85	30	460	290	10	10,5	19	190	6318 C3	6200-6318	6 x M10	3400	69,0
PDN 319	95	125	253	605	648	540	470,5	400	90	36	480	320	12	9,5	24	200	6319 C3	6200-6319	6 x M10	3200	83,0
PDN 320	100	130	264	635	673	570	500	400	95	40	500	320	8,5	11,5	24	215	6320 C3	6200-6320	6 x M10	3000	93,0

These housings are especially suitable for ventilation fans running with a higher speed than common pillow blocks. Since misalignment errors are largely excluded, ball bearings can be installed in these housings. The grease control discs on both sides simplify maintenance and throw excess grease into the middle of the large housing space.

Other application possibilities include: circular saws, milling machine shafts, belt drives or similar bearing applications.

6 possible bearing combinations allow it to be used for various requirements.

Efficient sealing against dust and dirt.