



Part No.	Dimensions (mm)																		Bearings	Spring Washer	Screws	Max. speed (rpm)	First fill (g)	Regreasing (g)	Weight (kg)
	d	da	H	H1	L2	L1	A	A1	A2	A3	L	V	H2	J1	J	w	N	D							
PDNB 306	24	30	50	100	210	340	226	171,5	140	240	160	40	18	150	130	45	15	75	6306 C3	6200-6306	4 x M6	9000	60	5	9,5
PDNB 307	28	35	60	116	239	394	260	195,5	160	274	190	45	18	175	150	49,5	15	80	6307 C3	6200-6307	4 x M6	8500	80	5	13,7
PDNB 308	32	40	60	121	298	491	315	255,5	214	331	190	52	20	225	150	53	15	90	6308 C3	6200-6308	4 x M6	7500	110	10	19,0
PDNB 309	38	45	70	137	340	536	360	279,5	236	376	210	52	22	250	170	63	15	100	6309 C3	6200-6309	4 x M6	6700	140	10	23,5
PDNB 310	42	50	70	142	360	613	377	311,5	266	393	210	60	25	275	170	59	15	110	6310 C3	6200-6310	6 x M6	6300	190	10	30,0
PDNB 311	48	55	80	158	400	658	422	335,5	288	438	260	60	25	300	210	69	19	120	6311 C3	6200-6311	4 x M8	5600	240	15	39,0
PDNB 312	48	60	80	165	437	696	460	383,5	334	476	260	70	25	340	210	68	19	130	6312 C3	6200-6312	6 x M8	5000	300	15	52,0
PDNB 313	55	65	95	185	470	728	492	402,5	349	508	280	70	25	360	230	74	19	140	6313 C3	6200-6313	6 x M8	4800	390	15	56,5
PDNB 314	60	70	95	190	490	812	512	420,5	365	532	290	70	25	380	230	76	19	150	6314 C3	6200-6314	6 x M8	4500	480	20	67,0
PDNB 315	65	75	100	200	508	847	547	448,5	389	567	320	80	30	400	260	83,5	19	160	6315 C3	6200-6315	6 x M8	4300	590	20	80,0
PDNB 316	70	80	112	220	525	856	556	466,5	403,5	576	320	80	30	420	260	78	19	170	6316 C3	6200-6316	6 x M10	3800	700	20	90,0
PDNB 317	75	85	112	225	559	890	590	486	422,5	610	350	80	30	440	290	85	19	180	6317 C3	6200-6317	6 x M10	3600	830	25	112,0
PDNB 318	80	90	112	230	575	965	605	510	446,5	625	350	85	30	460	290	82,5	19	190	6318 C3	6200-6318	6 x M10	3400	1000	25	130,0
PDNB 319	85	95	125	253	605	1008	648	540	470,5	668	400	90	36	480	320	94	24	200	6319 C3	6200-6319	6 x M10	3200	1150	30	150,0

These housings are especially suitable for ventilation fans running with a higher speed than common pillow blocks. Since misalignment errors are largely excluded, ball bearings can be installed in these housings. The grease control discs on both sides simplify maintenance and throw excess grease into the middle of the large housing space.

Other application possibilities include: circular saws, milling machine shafts, belt drives or similar bearing applications.

6 possible bearing combinations allow it to be used for various requirements.

Efficient sealing against dust and dirt.