



Item No.	Dimensions (mm)			Recommended mounting bolt size	Item No.	Dimensions (mm)			Recommended mounting bolt size
	N2	J1	J2			N2	J1	J2	
SSNHF 208-307 RH4	11	160	34	M8	SSNHF 508-607 RH4	11	160	34	M8
SSNHF 209 RH4	11	160	34	M8	SSNHF 509 RH4	11	160	34	M8
SSNHF 210 RH4	11	160	34	M8	SSNHF 510-608 RH4	11	160	34	M8
SSNHF 211 RH4	14	200	40	M12	SSNHF 511-609 RH4	14	200	40	M12
SSNHF 212 RH4	14	200	40	M12	SSNHF 512-610 RH4	14	200	40	M12
SSNHF 213 RH4	14	220	48	M12	SSNHF 513-611 RH4	14	220	48	M12
SSNHF 215 RH4	14	220	48	M12	SSNHF 515-612 RH4	14	220	48	M12
SSNHF 216 RH4	18	252	52	M16	SSNHF 516-613 RH4	18	252	52	M16
SSNHF 217 RH4	18	252	52	M16	SSNHF 517 RH4	18	252	52	M16
SSNHF 218 RH4	18	280	58	M16	SSNHF 518-615 RH4	18	280	58	M16
					SSNHF 519-616 RH4	18	300	66	M16
					SSNHF 520-617 RH4	18	320	74	M16
					SSNHF 522-619 RH4	18	320	74	M16
					SSNHF 524-620 RH4	18	330	74	M16
					SSNHF 526 RH4	22	370	80	M20
					SSNHF 528 RH4	26	400	92	M24
					SSNHF 530 RH4	26	430	100	M24
					SSNHF 532 RH4	26	450	100	M24

See the catalogue [SNHF](#) for the remaining dimensions and standard two elongated mounting bolt holes (LH2).

See the catalogue [SSNHF + SNHF GS Breaking loads](#) for breaking load data

Versions with four elongated mounting bolt holes can be found in the [SSNHF LH4](#) datasheet.

Also available as two drilled round mounting bolt holes, version [SSNHF RH2](#).