



Housing No.	Shaft		Dimensions (mm)											Mounting Bolt	Weight (kg)	Labyrinth Seals	Bearing	Adapter Sleeve	Fixing Rings	End cover	O-Ring \varnothing * Length	Grease Qty First filling		
	d	D _a	C _a	A	A ₁	H	H ₁	H ₂	L	J	J ₁	x	N										N ₁	S
SD 3036 TS	160	280	108	230	180	333	170	70	510	430	100	78	34	28	14	M24	69,5	TS 36	23036 K	H 3036	2 x FR 280-17	ETS36	4 x 560	1,2 kg
SD 3038 TS	170	290	115	240	190	353	180	75	530	450	110	83	34	28	15	M24	77,5	TS 38	23038 K	H 3038	4 x FR 290-10	ETS38	4 x 590	1,5 kg
SD 3040 TS	180	310	122	260	210	375	190	80	560	480	120	88	34	28	10	M24	97,5	TS 40	23040 K	H 3040	4 x FR 310-10	ETS40	4 x 620	2,0 kg
SD 3044 TS	200	340	130	280	230	411	210	85	610	510	130	93	42	35	10	M30	123	TS 44	23044 K	H 3044	4 x FR 340-10	ETS44	4 x 680	2,7 kg
SD 3048 TS	220	360	140	290	240	434	220	90	640	540	140	100	42	35	12	M30	139	TS 48	23048 K	H 3048	4 x FR 360-12	ETS48	4 x 750	3,0 kg
SD 3052 TS	240	400	148	310	260	474	240	95	700	600	150	106	42	35	12	M30	187	TS 52	23052 K	H 3052	2 x FR 400-22	ETS52	4 x 810	3,9 kg
SD 3056 TS	260	420	166	320	280	516	260	100	770	650	160	116	50	42	13	M36	221	TS 56	23056 K	H 3056	6 x FR 420-10	ETS56	4 x 870	4,9 kg
SD 3060 TS	280	460	166	320	280	551	280	105	790	670	160	119	50	42	16	M36	252	TS 60	23060 K	H 3060	2 x FR 460-24	ETS60	4 x 940	5,2 kg
SD 3064 TS	300	480	181	350	310	591	300	110	830	710	190	125	50	42	22	M36	301	TS 64	23064 K	H 3064	6 x FR 480-10	ETS64	4 x 1000	7,0 kg
SD 3068 TS	320	520	197	370	330	631	320	115	880	750	200	-	50	42	23	M36	339	TS 68	23068 K	H 3068	4 x FR 520-16	ETS68	4 x 1050	8,7 kg
SD 3072 TS	340	540	198	370	330	631	320	115	880	750	200	-	50	42	23	M36	339	TS 72	23072 K	H 3072	4 x FR 540-16	ETS72	4 x 1090	10,9 kg
SD 3076 TS	360	560	180	400	360	675	340	120	950	810	220	-	50	42	24	M36	427	TS 76	23076 K	H 3076	2 x FR 560-22,5	ETS76	4 x 1150	10,9 kg
SD 3080 TS	380	600	192	400	360	695	350	120	1000	840	220	-	50	42	30	M36	454	TS 80	23080 K	H 3080	2 x FR 600-22	ETS80	4 x 1220	11,7 kg

These Housings can also be manufactured of ductile iron or cast steel. Special kevlar or felt seals on request.