



Angular Contact Ball Bearing 7300



Type	Dimensions (mm)				Basic radial load rating (N)		Speed (1/min)	
	d	D	B	m (kg)	Dynamic	Static	Limiting	Reference
7301	12	37	12	0,066	10600	5300	24000	19000
7302	15	42	13	0,081	13200	7200	20000	17000
7303	17	47	14	0,110	16300	9000	18000	15000
7304	20	52	15	0,143	19000	11100	17000	13000
7305	25	62	17	0,242	26000	15800	14000	11000
7306	30	72	19	0,341	33000	2210	11000	10000
7307	35	80	21	0,447	40000	27500	9500	9000
7308	40	90	23	0,646	50000	34500	8500	8500
7309	45	100	25	0,813	61000	43000	7500	7500
7310	50	110	27	1,130	70000	50000	7000	7000
7311	55	120	29	1,460	80000	61000	6300	6700
7312	60	130	31	1,740	90000	69000	5600	6300
7313	65	140	33	2,120	103000	82000	5300	6000
7314	70	150	35	2,580	117000	93000	5000	5600
7315	75	160	37	3,290	130000	107000	4500	5300
7316	80	170	39	3,660	144000	124000	4300	4800
7317	85	180	41	4,400	155000	138000	4000	4500
7318	90	190	43	5,140	167000	155000	3800	4300
7319	95	200	45	5,930	176000	167000	3800	4000
7320	100	215	47	7,160	199000	197000	3600	3600
7321	105	225	49	9,000	209000	214000	5300	3400
7322	110	240	50	9,970	232000	245000	3400	3200
7324	120	260	55	12,500	255000	285000	3200	3000
7326	130	280	58	15,100	285000	325000	3000	2600
7328	140	300	62	20,500	300000	345000	4300	2400
7330	150	320	65	24,800	325000	390000	3800	2200
7332	160	340	68	29,000	360000	450000	3600	2000
7334	170	360	72	34,400	405000	530000	3200	1900