



Axial Spherical Roller Bearing 29400



Type	Dimensions (mm)						Radial load rating (N)		Speed (1/min)
	d	D	T	D ₁	d ₁	m (kg)	Dynamic	Static	Limiting
29412	60	130	42	88	115	2,23	335000	900000	3400
29413	65	140	45	94	125	3,03	380000	1020000	3400
29414	70	150	48	102	135	3,71	430000	1200000	3000
29415	75	160	51	108	140	4,40	490000	1370000	2800
29416	80	170	54	116	150	5,28	550000	1560000	2800
29417	85	180	58	123	160	5,89	600000	1730000	2600
29418	90	190	60	130	170	7,38	670000	1930000	2400
29420	100	210	67	142	185	10,00	830000	2450000	2200
29422	110	230	73	158	205	13,10	950000	2800000	2000
29424	120	250	78	172	220	16,30	1120000	3350000	1800
29426	130	270	85	187	240	19,00	1250000	3900000	1700
29428	140	280	85	194	250	21,90	1290000	4050000	1700
29430	150	300	90	211	270	26,90	1460000	4800000	1500
29432	160	320	95	224	285	31,60	1660000	5300000	1400
29434	170	340	103	239	305	39,20	1860000	6000000	1300
29436	180	360	109	253	320	46,20	2080000	6800000	1300
29438	190	380	115	268	340	54,90	2320000	7500000	1200
29440	200	400	122	282	360	64,70	2550000	8500000	1100
29444	220	420	122	303	375	67,40	2600000	8500000	1100
29448	240	440	122	321	400	73,50	2700000	9500000	1100
29452	260	480	132	353	435	93,60	3100000	11000000	1000
29456	280	520	145	380	470	121,00	3650000	12900000	900
29460	300	540	145	398	490	129,00	3900000	14000000	900
29464	320	580	155	432	525	158,00	4300000	15600000	800
29468	340	620	170	458	560	200,00	5200000	19000000	750