



Item No.	Dimensions (mm)			Basic radial load rating (N)		Speed (1/min)		Weight (kg)
	d	D	B	Dynamic Cr	Static Cor	Limiting	Reference	
<b>21304</b>	20	52	15	36.450	30.150	15.000	12.000	0,16
<b>21305</b>	25	62	17	46.800	38.700	13.000	10.000	0,25
<b>21306</b>	30	72	19	64.800	56.700	11.000	8.500	0,39
<b>21307</b>	35	80	21	74.700	66.150	9.500	8.000	0,50
<b>21308</b>	40	90	23	97.200	95.400	7.500	7.000	0,70
<b>21309</b>	45	100	25	116.100	116.100	6.700	6.700	0,85
<b>21310</b>	50	110	27	116.100	116.100	6.700	6.300	1,28
<b>21311</b>	55	120	29	153.000	149.400	6.300	5.600	1,19
<b>21312</b>	60	130	31	190.800	205.200	6.300	4.500	1,78
<b>21313</b>	65	140	33	225.000	243.000	5.000	4.800	2,42
<b>21314</b>	70	150	35	225.000	243.000	5.000	4.800	3,00
<b>21315</b>	75	160	37	274.500	292.500	4.800	4.300	2,86
<b>21316</b>	80	170	39	274.500	292.500	4.800	4.300	2,65
<b>21317</b>	85	180	41	310.500	337.500	4.800	3.800	5,37
<b>21318</b>	90	190	43	342.000	373.500	4.500	3.600	6,26
<b>21319</b>	95	200	45	387.000	409.500	4.000	3.400	6,63
<b>21320</b>	100	215	47	441.000	477.000	3.600	3.200	8,19
<b>21322</b>	110	240	50	540.000	576.000	3.000	2.800	11,10