



| Item No. | Dimensions (mm) | | | Basic radial load rating (N) | | Speed (1/min) | | Weight (kg) |
|--------------|-----------------|-----|-------|------------------------------|------------|---------------|-----------|-------------|
| | d | D | B | Dynamic Cr | Static Cor | Limiting | Reference | |
| 23218 | 90 | 160 | 52,4 | 396.000 | 468.000 | 4.300 | 2.800 | 4,3 |
| 23220 | 100 | 180 | 60,3 | 495.000 | 589.500 | 3.600 | 2.400 | 6,3 |
| 23222 | 110 | 200 | 69,8 | 639.000 | 778.500 | 3.000 | 2.200 | 9,2 |
| 23224 | 120 | 215 | 76,0 | 733.500 | 918.000 | 2.800 | 1.900 | 11,5 |
| 23226 | 130 | 230 | 80,0 | 810.000 | 1.026.000 | 2.600 | 1.800 | 13,4 |
| 23228 | 140 | 250 | 88,0 | 972.000 | 1.260.000 | 2.400 | 1.600 | 17,7 |
| 23230 | 150 | 270 | 96,0 | 1.143.000 | 1.494.000 | 2.200 | 1.400 | 22,9 |
| 23232 | 160 | 290 | 104,0 | 1.314.000 | 1.710.000 | 2.200 | 1.300 | 28,6 |
| 23234 | 170 | 310 | 110,0 | 1.467.000 | 1.944.000 | 2.000 | 1.200 | 34,9 |
| 23236 | 180 | 320 | 112,0 | 1.530.000 | 2.124.000 | 2.000 | 1.100 | 37,2 |