



Item No.	Dimensions (mm)									Basic Load Ratings (kN)		Limiting Speed (RPM)		Weight (kg)
	d	D	T	B	C	r	da (min)	db (max)	Da (max)	Dynamic Radial	Static Radial	Grease	Oil	
33005	25	47	17	17	14,0	0,6	33	29	42	31,0	38,0	8.000	11.000	0,13
33006	30	55	20	20	16,0	1,0	39	35	49	42,0	54,0	6.700	9.000	0,21
33007	35	62	21	21	17,0	1,0	44	40	56	49,0	65,0	5.600	8.000	0,27
33008	40	68	22	22	18,0	1,0	49	45	62	59,0	81,5	5.300	7.100	0,32
33009	45	75	24	24	19,0	1,0	54	51	69	69,0	99,0	4.800	6.300	0,41
33010	50	80	24	24	19,0	1,0	59	55	74	70,5	104,0	4.300	6.000	0,45
33011	55	90	27	27	21,0	1,5	66	62	81	91,5	138,0	3.800	5.300	0,66
33012	60	95	27	27	21,0	1,5	71	66	86	96,0	150,0	3.600	5.000	0,71
33013	65	100	27	27	21,0	1,5	76	71	91	97,5	156,0	3.400	4.500	0,76
33014	70	110	31	31	25,5	1,5	81	78	101	127,0	204,0	3.000	4.300	1,11
33015	75	115	31	31	25,5	1,5	86	83	106	133,0	220,0	3.000	4.000	1,18
33016	80	125	36	36	29,5	1,5	91	88	116	172,0	282,0	2.800	3.600	1,66
33017	85	130	36	36	29,5	1,5	96	94	121	180,0	305,0	2.600	3.600	1,75
33018	90	140	39	39	32,5	2,0	102	99	131	220,0	360,0	2.400	3.200	2,21
33019	95	145	39	39	32,5	2,0	107	103	136	231,0	390,0	2.400	3.200	2,30
33020	100	150	39	39	32,5	2,0	112	107	141	235,0	405,0	2.200	3.000	2,38
33021	105	160	43	43	34,0	2,5	120	115	150	256,0	435,0	2.000	2.800	3,03
33022	110	170	47	47	37,0	2,5	125	121	160	294,0	515,0	2.000	2.600	3,84
33024	120	180	48	48	38,0	2,5	135	130	168	300,0	540,0	1.800	2.600	4,20
33026	130	200	55	55	43,0	2,5	145	144	188	395,0	715,0	1.700	2.200	6,25
33028	140	210	56	56	44,0	2,5	155	153	198	410,0	770,0	1.600	2.200	6,74
33030	150	225	59	59	46,0	3,0	168	165	213	435,0	805,0	1.400	2.000	8,07