



Outer ring with single split in axial direction.

Inner ring with cylindrical extensions at both sides.

Lubrication grooves and holes in the outer and inner rings.

Outer ring with lip seals in both sides.

Both outer and inner rings are properly phosphate treated.

Part No.	Dimensions (mm)									Load ratings (kN)		Weight (kg)
	d	d <sub>2</sub>	D	B	C	d <sub>k</sub>	R <sub>15 min</sub>	R <sub>25 min</sub>	α	dyn. C	stat. C0	
GE17HO.2RS	17	21	30	21	10	25	0,2	0,3	3	21,2	106	0,04
GE20HO.2RS	20	24	35	24	12	29	0,2	0,3	3	30	146	0,069
GE25HO.2RS	25	29	42	29	16	35,5	0,2	0,6	3	48	240	0,12
GE30HO.2RS	30	34	47	30	18	40,7	0,2	0,6	3	62	310	0,15
GE35HO.2RS	35	40	55	35	20	47	0,3	1	3	80	400	0,26
GE40HO.2RS	40	45	62	38	22	53	0,3	1	3	100	500	0,32
GE45HO.2RS	45	52	68	40	25	60	0,3	1	3	127	640	0,43
GE50HO.2RS	50	57	75	43	28	66	0,3	1	3	156	780	0,55
GE60HO.2RS	60	68	90	54	36	80	0,3	1	3	245	1220	1,1
GE70HO.2RS	70	78	105	65	40	92	0,3	1	3	315	1560	1,6
GE80HO.2RS	80	90	120	74	45	105	0,3	1	3	400	2000	2,5